

WORKS BARRICADE

BLOW MOLDED PLASTIC PANELS WITH GALVANIZED LEGS
TD2225 MODEL

NCHRP350 CRASH TEST CERTIFIED
AND MEETS MUTCD STANDARDS



NCHRP350 Approved: WZ-54

FEATURES:

- Type I and Type II can be purchased as assembled units or component parts. Legs and boards can be purchased separately. All barricade components are completely interchangeable.
- Legs are standard 45" manufactured using galvanized steel in 12 and 14 gauge thickness.
- Barricades are assembled utilizing 1/4" x 1" galvanized carriage bolts, high bend mil spec split lock washers with locknuts. Legs are hinged with two 1/2-13 X 1" hex bolts and 1/2-13 nylon locknuts.
- High Impact Blow Molded plastic panels are reinforced to reduce bending and warping.

All sheeting complies with ASTM 4956 requirements.

COLORS AVAILABLE:

The TD2225 Works Barricades is currently available in White. Three D Traffic Works can manufacture this product to your desired color.

GENERAL INFORMATION:

General information is listed on the reverse side. The measurements provided are intended only as a source of information. They are given without guarantee and are not classified as a warranty. A specification will be sent to you upon request.





TD2225 MODEL

WORKS BARRICADE BLOW MOLDED PLASTIC PANELS WITH STEEL LEGS

SPECIFICATIONS

- **Folded Dimensions:**
 Height: 45".
 Length: 24".
 Folded Thickness: 2.300"
- **Plastic Board Thickness:**
 0.560 Inches
- **Plastic Board Material:** UV Stabilized Polymer Compound with Cold Weather Protection Package with 90% Recycled Content.
- **Leg Material:** 14 and 12 Gauge Galvanized Steel Roll Form.

